
TROUBLESHOOTING & PUMP ALARMS

STEP BY STEP GUIDE



- Read the screen
- **2** Press the START/STOP button to silence the alarm
- 3 See overleaf for a list of reasons why your pump is alarming and how to deal with each alarm




ALARM	REASON	SOLUTION
NO SET	The set is not fitted or is fitted incorrectly	Reinsert the giving set as per instructions
	The pressure sensor is dirty	Clean the sensors and reinsert cassette
DOOR	Door is broken, cracked or not closed	Make sure the door is closed Tape door to pump tightly to continue feeding and call your Nutricia Homeward Customer Service team to arrange for a replacement
PROG	Flow rate has not been programmed	Make sure the correct flow rate is programmed
PUSH START	The pump has been paused for three or more minutes	By pressing the START/STOP button to silence the alarm, a further three minute pause commences. When ready to restart feeding press the START/ STOP button
AIR	Air bubble in the giving set	Disconnect the giving set from the feeding tube and hold over a clean container. Press the FILL SET button until the air bubble has passed out of the giving set. Press FILL SET to stop, reattach to feeding tube and press START
	The bag of feed is empty	If further feeding is required, replace the empty bag of feed and recommence feeding. If you need to refill the giving set with feed, follow solution instructions for "air bubble in the giving set". If required dose delivered, switch off pump and discard feed and giving set as per training
	The air sensor is dirty	Clean the sensor area following the cleaning guidelines

ALARM	REASON	SOLUTION	
END OF DOSE	The pump has administered the dose	Press and hold the ON/OFF button until it beeps and is powered off	
		If the END OF DOSE alarms inappropriately contact your Nutricia Homeward Enteral Nurse Specialist or the Out of Hours Advice Line	
OCC IN	The pump detected an occlusion between the feed and the pump	Make sure there are no kinks in the tubing, that clamps are not closed between the feed container and the pump, and that the foil has been pierced	
	The sensor is dirty	Clean the sensor area (see cleaning guidelines), reinsert the giving set in the pump and restart the pump	
	The pump detected an occlusion between the pump and the patient	If relevant, make sure the clamp is open	
оссоит		Make sure there are no kinks in the giving set or feeding tube	
	The sensor is dirty	Clean the sensor area (see cleaning guidelines), reinsert the giving set in the pump and restart the pump	
Disease refer to the step by step guide an acut was a			

Please refer to the step by step guide on next page →


CAUTION: Do not use the 'FILL SET' function when there is a set occlusion as this may cause the pump to incorrectly calibrate

HOW TO STOP THE OCC ALARM



- Press the START/STOP button
- 2 Detach the giving set
- 3 Solve the occlusion problem (see below)
- 4 Re-insert the giving set and close door
- **5** Press the START/STOP button

THE MOST COMMON SET OCCLUSION



ALARM	REASON	SOLUTION
BATT	The battery capacity is running low. There is approximately one hour of feeding left when a rate of 125ml/hour is set	Connect the pump to the electrical supply and charge for 6 hours. The pump can be used while connected to the electrical supply
BATT 'E' 'F'	The battery has failed	Contact your Nutricia Homeward Customer Service team to arrange for the pump to be serviced
LOCK	The current feeding regimen has been locked into the machine to prevent accidental changing of regimen	Contact your Nutricia Homeward Enteral Nurse Specialist
ERROR with a number, e.g. ERROR 12	The self test detected a fault	Contact your Nutricia Homeward Enteral Nurse Specialist to arrange for the pump to be serviced



Nutricia Advanced Medical Nutrition White Horse Business Park, Trowbridge, Wiltshire BA14 0XQ www.nutriciaflocare.com SCC3297-09/17

